



RTXM191-647~661 1.25Gb/s SFP

PIN
EEPROM

- CWDM DFB
- 1.25Gb/s
-
-
- DDM
-
- 0~70
- 80km
- RoHS

-
- 1G
-
-

- SFP MSA (INF-8074i)
- SFF-8472
- IEEE802.3z
- FC-Pi v2.0

1	I _{cc}	mA	-	-	300	
		mV	150		1100	
		mV	300	-	600	
TX_fault /LOS	(TTL)	VOH	V	2.0	-	V _{cc}
		VOL	V	0	-	0.8
TX_disable	(TTL)	VOH	V	2.0	-	V _{cc}
		VOL	V	0	-	0.8
	P _o	dBm	0		+3	
2	λ _c	nm	λ-6.5		λ+6.5	
	EX	dB	9			
	SMSR	dB	30			
(-20dB)	Δλ	nm			1	
3	TJ	UI			0.284	
4	RIN	dB/Hz			-120	
	GE					
/	Trise/Tfall	ps			260	
	-	dB			2	
	P _{off}	dBm			-45	
	λ _c	nm	1250		1620	
5	S	dBm			-24	
	Pin	dBm	-3			
		dBm			-24	
			-35			

		dB	0.5		5
Note1.					
Note2.	CWDM		1471, 1491, 1511, 1531, 1551, 1571, 1591,		
			1611nm		
Note3.					
Note4.	RIN				
					12dB
Note5.	PRBS	1.25Gb/s	EX=10dB		

RTXM191-647	SFP	1.25G	1471nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS
RTXM191-649	SFP	1.25G	1491nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS
RTXM191-651	SFP	1.25G	1511nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS
RTXM191-653	SFP	1.25G	1531nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS
RTXM191-655	SFP	1.25G	1551nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS
RTXM191-657	SFP	1.25G	1571nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS
RTXM191-659	SFP	1.25G	1591nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS
RTXM191-661	SFP	1.25G	1611nm DFB	0 ~ +3dBm	PIN	-24dBm	0~70	80km	DDM, RoHS