



330-551	25.78	/	-8472
-8402,	-8432	-8431	-8472
	2		
●	100 (4)		
●			
●	<1.2		
●	0 70		
●	+3.3 5%		
●	-8472		
●	25 A -		
●	-8472		
●	-8402		
●	-8432		
●	-8431		

			840		860
	$\Delta\lambda$				0.6
A			-6.4		3
			-8.4		2.4
			2		
					5
A					-30
			840		860
A			-10.3		2.4
(A)					-5.2
					-12
A			-30		
-A					-13

										A
		(/)		()		(A)		()		
RTXM330-551	SFP+	25.78	VCSEL	-8.4 2.4	PIN	< -5.2	0~70 °C	100m	DDM	25 A -

	V_{CC}		3.14	3.3	3.46
	I_{CC}	A			350
Transmitter					
	R_{IN}		80	100	120
	V_{IN}	-	90		800
	V_{DIS}		2		V_{CCHOST}
	V_{EN}		V_{EE}		$V_{EE}+0.8$
A	V_{FA}		2.2		V_{CCHOST}
-A	V_{FDA}		V_{EE}		$V_{EE}+0.4$
Receiver					
	V_{OD}	-	185		425
	V_{LOSFT}		2.2		V_{CCHOST}
	V_{LOSNR}		V_{EE}		$V_{EE}+0.4$